

# VAPOUR

## SINGLE LENS VAPOUR

Vapour (single lens) is a versatile low profile and lightweight goggle. Vapour features a single 3mm polycarbonate lens, indirect lower vents with 2mm closed cell foam and a 35mm head strap with 'out-riggers' for greater flexibility under hard hats.



Clear Frame With SBR Foam  
/ Single Clear Lens / Indirect  
Lower Vents • 1650401



Smoke Frame With SBR Foam  
/ Single Smoke Lens / Indirect  
Lower Vents • 1650402



91g

### ACCESSORIES



- 1650016 • RX Adaptor
- 1650413 • Clear Single Lens Only
- 1650414 • Smoke Single Lens Only

- + LOW PROFILE, LIGHTWEIGHT TPR FRAME**
- + SINGLE 3.0MM POLYCARBONATE LENS**
- + LARGE ADJUSTABLE STRAP**
- + INDIRECT LOWER VENTS WITH 2MM CLOSED CELL FOAM**
- + OPTIONAL PRESCRIPTION RX ADAPTOR AVAILABLE**
- + SPLASH APPROVED**

**bolle**  
SAFETY

# VAPOUR

## SINGLE LENS VAPOUR

| MODEL  | VERSIONS   | REFERENCES | LENS MARKING | FRAME MARKING      | COATINGS              |
|--------|--|------------|--------------|--------------------|-----------------------|
| VAPOUR |  Clear Frame with SBR Foam / Single Clear Lens / Indirect Lower Vents | 1650401    | CIO          | AS/NZS 1337.1:2010 | Anti-scratch/Anti-fog |
|        |  Smoke Frame with SBR Foam / Single Smoke Lens / Indirect Lower Vents | 1650402    | CI3          | AS/NZS 1337.1:2010 | Anti-scratch/Anti-fog |

### LENS MARKING

- C.** The letter 'C' signifies that the product has been tested and approved for use against splashes and is appropriate for chemical handling.
- I.** The letter 'I' signifies 'Medium Impact' approval.
- O.** The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

### OCULAR LENS CATEGORY:

- O.** Range of luminous transmittance 80-100% (clear).
- 3.** Range of luminous transmittance 8 -18% (smoke).

### APPLICATIONS

- Chemical splash protection
- Dust protection
- Spraying
- Acid and alkaline handling
- Engineering
- Milling
- Process work

### MAIN MARKETS

- Petrochemical industry
- Mining
- Construction
- Paint
- Manufacturing

### LENSES

- 'ALS' anti-fog/anti-scratch coating on both sides of clear lens
- 99.9% UV 385 - Clear
- 99.9% UV 400 - Smoke

### FRAME MARKING

**AS/NZS 1337.1:2010** : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

| CHARACTERISTICS |                |
|-----------------|----------------|
| LENSES          | PC 3.0mm       |
| FRAME           | TPR            |
| TEMPLES         | Non applicable |
| STRAP           | Yes            |
| FOAM            | Yes            |
| SPARE LENSES    | No             |

#### ASIA/PACIFIC HEADQUARTERS:

Bollé Safety AU Pty Limited  
32-40 Fairchild Street  
Heatherton VIC 3202  
T: 1300 138 098  
E: safety@bolle.com.au

[bollesafety.com.au](http://bollesafety.com.au)

#### NEW ZEALAND:

T.: 0800 2655 369  
E: bolle@bolle.co.nz

**bolle**  
SAFETY